

# Network Zone Configuration

Below are the current configuration settings in the WRL Network Zone that are either pushed down to all Institution Zones, or that affect Network Zone linked bibliographic records.

<b>Configuration Area</b>	<b>Configuration Page</b>	<b>Parameter</b>	<b>Value</b>	<b>Notes</b>
Resources	Cataloging > Metadata Configuration > MARC21 Bibliographic Profile	Extensions	Field 081 Field 590 Field 012 Field 019 Field 029 Field 891	The fields listed in the Value column are ones that have been added or edited in the WRLC NZ; these are applied to NZ-linked records in the Metadata Editor. For more information, see the <i>Metadata Editor Warnings</i> page.
Resources	General > Other Settings	authority_ptc_ignore_suffix	LCNAMES, LCSH, LCGFT	Corrects bibliographic headings based on authority cross-references for the vocabularies listed, updating them to the preferred term and changing the field tag in the bibliographic record accordingly (such as, from 610 to 630).
Resources	General > Other Settings	avid_fuzzy_search_resolving	true	When set to <b>true</b> , enables the institution to indicate to Alma to avoid "Fuzzy matches" ("title only" matches) attempts if other information (like identifiers or author) exists in the URL.

Resources	General > Other Settings	cdi_consortia)inheritance	N	When set to N, no inheritance will occur for CDI search activations and full text activations of database type of collections from the network zone. All member institutions that are part of the consortium inherit full text activations for <i>collections with portfolios</i> from the Network Zone. It is not possible to not inherit Network Zone activations for these types of collections.
Resources	General > Other Settings	non_serial_match_profile	com.exlibris.repository.mms.match.CDLMatchingProfile	Value must be the same in both the NZ and the IZ. For more information, see <i>Match Profile in the Metadata Editor</i> page.
Resources	General > Other Settings	serial_match_profile	com.exlibris.repository.mms.match.CDLSMatchingProfile	Value must be the same in both the NZ and the IZ. For more information, see the <i>Match Profile in the Metadata Editor</i> page.
Resources	General > Other Settings	delete_nz_bib_records_with_relations_new_behavior	true	This value allows for cross-consortial checks for related records when the record is being deleted. For more information, see the <a href="#">Bibliographic Record Deletion - Related Records</a> page.

Resources	General > Other Settings	ignore_cz_records	true	If this parameter is set to true, Alma matches incoming records with any record that exists in the catalog and ignores bibliographic records that are linked to the Community Zone.
Resources	General > Other Settings	network_description_templates_rules_precedence	true	For more information, see the <i>Item Description Templates</i> page.
Resources	General > Other Settings	share_item_usage_across_network	true	When set to True in the Network Zone, then upon network search results, item usage data is shared for all network's members in the <b>Physical Usage</b> tab.
Resources	General > Other Settings	show_version_cataloger_name_for_other_members	true	When set to True in the Network Zone, the name of the cataloger will appear in the Metadata Editor when viewing previous versions of a record.
Resources	General > Description Templates	Network Rules List	For a full list of all WRLC description templates, see the <i>Item Record Description Policies and Templates</i> page	For more information, see the <i>Item Description Templates</i> page.
Resources	General > Authority Control Rules	Link BIB Headings tab	For a full list of all rules configured in the WRLC NZ, see the <i>Authority Control</i> page.	
Resources	General > Authority Control Rules	Preferred Term Correction tab	For a full list of all rules configured in the WRLC NZ, see the <i>Authority Control</i> page.	

Discovery	Search Configuration > Secondary Resource Type		For a full list of all secondary resource types configured in the WRLC NZ, see the <i>Secondary Resource Types</i> page.	These settings are applied to NZ-linked bibliographic records.
Discovery	Display Configuration > Resource Types Configuration		For a full list of all custom resource types configured in the WRLC NZ, see the <a href="#">Resource Types Configuration</a> page.	These settings are applied to NZ-linked bibliographic records.
Fulfillment	For a full list of all NZ-managed configurations for the Automated Fulfillment Network (AFN)/WRLC Consortium Loan Service (CLS), please see the <a href="#">AFN Network Zone Configurations</a> page			

---

Revision #8

Created 21 December 2023 15:16:34 by Jackie Saavedra

Updated 7 May 2025 14:28:09 by Jackie Saavedra